

TORO.

Count on it.

EVOLUTION® Series

Controllers

Introducing the next generation in controllers!

With an intuitive interface and exclusive features for “smart” control, the new Toro® EVOLUTION® is an easy choice for residential and light-commercial applications.

Features & Benefits

Revolutionary Interface

The EVOLUTION controller’s user interface was designed with the customer in mind. Shortcut buttons provide quick access to basic functions while the advanced menu leverages the experience and knowledge of the irrigation professional, all shown on a graphics display that navigates similar to many modern consumer electronic devices.

Easy Upgrade to Integrated Smart Control

An optional Smart Connect™ device plugs into the timing mechanism, enabling it to wirelessly communicate directly with a number of add-on devices—including a weather sensor, handheld remote, multiple soil sensors, and up to two wireless relays.

Computer-programmable with USB Drive

Simple-to-use software allows you to program everything at a computer. Use a standard USB drive to transfer programming to one or more controllers in a matter of seconds. Create your own schedules or utilize the easy to use wizard to generate a schedule based on the historical requirements of your location.



EPA WaterSense® Certified when used with Smart Connect™ Wireless Weather Sensor



Modular configurations
from 4 to 16 stations



12-station configuration with
(2) 4-station modules



16-station configuration with (1)
12-station module

Controller Interface

The EVOLUTION controller's interface is a system of informative yet easy-to-understand screens that are quickly accessible using the controller's shortcut buttons.

Dedicated Water OFF

Homeowner Basic Operations

Help/Info


Contractor Advanced Operations



Standard Functions



The **Standard** menu gives the homeowner access to the most fundamental functions of the controller, such as manual watering, setting watering days and start times for a *single* schedule, and adjusting the amount of irrigation, all directly accessible through dedicated shortcut buttons.



For example, the **Water Now Screen** allows the user to begin watering with as few as just two button presses, with the option of starting a specific schedule, specific zone, or watering all zones in series.




Another example is the **Review Screen**, which is an at-a-glance summary showing which days the controller is going to water in the next seven days for the schedule you select.

Advanced Functions



The **Advanced** menu gives the contractor access to the full power of the EVOLUTION® controller, including the ability to set up *multiple* irrigation and auxiliary schedules, create custom grow-in schedules, and configure any "smart" add-on devices - all operations that may otherwise overwhelm a homeowner.



For example, the **Apply Sensors** screen allows the user to easily view and configure all the sensors available to the controller, including rain, ET, and soil.



The **Grow In Screen** allows the user to set up a grow-in schedule for a user-defined period of time (up to 90 days), after which the controller will default back to its normal irrigation schedule(s).

Other Examples



The **Home Screen** displays the current time and date, what zones are scheduled to water next, or if currently watering, what zone(s) are currently watering and how much time is remaining, as well as any alerts – in the absence of any alerts, the screen will display "SYSTEM OK."



The **Contractor Message Screen** allows the contractor to input a custom message with their name and contact information into the controller from the software via a USB drive so it is visible to the homeowner when they press the "Help" button.

Smart Connect™ Add-On Devices

Simply plugging the Smart Connect device into the EVOLUTION® controller allows it to communicate wirelessly with a number of add-on devices, providing a great opportunity to upgrade with a number of different water-saving and time-saving options.



Wireless ET Sensor

Uses live temperature and solar measurements as well as historical weather data for your location to calculate the amount of water needed from the irrigation system.



Handheld Remote

Makes maintenance checks a snap, allowing you to run sprinklers or schedules from up to 1000 feet (305 m) away.



Toro® Smart Connect™ Plug-In Receiver

Installs easily on the backside of the EVOLUTION® controller's front panel. No wires, No externally mounted receiver. One Smart Connect™ Receiver is all that is required to communicate to all Add-On Devices.



Toro® Precision™ Soil Sensor

Up to three soil sensors can be used (one per schedule) to monitor the moisture level in the soil and prevent over- and underwatering. With up to a 500 feet (152,4 m) wireless range, there's no digging required to install.



EVOLUTION® Scheduling-Advisor™ Software*

Programming can be transferred from your computer to the controller in seconds using a standard USB drive.

*Smart Connect device not required for software programming capability.



Wireless Auxiliary Relay

Up to two wireless relays can be used to turn on lighting, pumps, or fountains, just to name a few possibilities.

Dimensions

- 11.25" W x 7.75" H x 4.5" D (286 x 197 x 114 mm)
- Weight: 4.5 lbs. (2 kg)

Electrical Specifications

- Electrical input power:
 - 120 VAC
 - 30 VA maximum
 - UL, CUL Listed
- Station output power:
 - 24 VAC
 - 0.75 amps per station maximum
 - 0.75 amps pump/master valve
 - 1.0 amps total load
- Surge Protection:
 - 6.0 KV common mode; 1.0 KV normal mode
- Operation of two solenoids per station (up to 0.75 amps per station max)

Programming

- One schedule in the default "standard" mode
- Up to six schedules in "advanced" mode:
 - Three irrigation schedules, four start times per schedule
 - One fixed auxiliary schedule, plus two wireless (optional Add-on)
- Three scheduling choices:
 - Seven-day calendar
 - 1- to 30-day interval with up to seven day restrictions
 - Odd/even days with up to seven day restrictions
- Monthly season adjust by schedule
- Schedule stacking, with automatic split cycle when season adjust is greater than 100%
- Grow-in schedule settable up to 90 days automatically reverts to regular irrigation schedule
- Station runtimes from one minute to twelve hours
- Allows 30, 60, or 90 second manual runtimes for things such as winterization/blowouts
- Programmable well-recovery/station-delay from 10 seconds to 30 minutes
- Pump start delay from 10 seconds to 30 minutes
- Master valve on/off by zone
- Timed water off from one to fourteen days
- Compatible with normally-closed rain sensors
- Automatic short detection for circuit protection and faster troubleshooting
- Non-volatile memory doesn't require batteries and holds programming for up to five years
- Zone Diagnostic Test which displays current values, short, over current or open zones

Hardware

- 4 to 16 stations with 4- and 12-station hot-swappable modules
- Cabinet easily mounts to the wall through two easily-accessible screw holes on the upper left-hand and right-hand sides of the controller
- Red LED next to display lights in the event of an alert
- 128 x 64 pixel graphical display
- Battery on the timing mechanism for "armchair" programming
- Outdoor key-lock cabinet manufactured out of durable UV-resistant plastic and includes standardized key used on many of the most popular controllers
- Indoor cabinet includes internal transformer with pre-attached pigtail

Optional Add-ons and Accessories

- EVO-SC – Smart Connect™ Device
- PSS-SEN – Precision™ Soil Sensor Probe
- EVO-WS – ET/Weather Sensor
- EVO-HH – Maintenance Remote
- EVO-AR – Auxiliary Relay

Warranty

- Five years

EVOLUTION® Series Model List

Model	Description
• EVO-4ID	4-station Indoor Controller
• EVO-4OD	4-station Outdoor Controller

Add-ons and Accessories

Model	Description
• EMOD-4	4-station Expansion Module
• EMOD-12	12-station Expansion Module
• EVO-SC	Smart Connect™ Plug-In Receiver
• PSS-SEN	Wireless Precision™ Soil Sensor Probe Only
• EVO-WS	Wireless Weather Sensor
• EVO-HH	Wireless Handheld Maintenance Remote
• EVO-AR	Wireless Auxiliary Relay

Specifying Information

EVO-4-XX-XX-SC			
Description	Cabinet Type	Module	Connector Options
EVO-4	XX	XX	SC
EVO-4 – EVOLUTION Controller	ID – Indoor OD – Outdoor	4 – 4-station 12 – 12-station	SC – Smart Connect Device
Example: A 16-station EVOLUTION controller in an indoor cabinet with the Smart Connect device would be specified as EVO-4ID-12-SC			

